

A 3D Spectral Integral Method for Layered Media

Ergun Simsek*, Jianguo Liu, and Qing H. Liu

Electrical and Computer Engineering, Duke University,

Durham, NC 27705, <http://www.ee.duke.edu>

Email: qhliu@ee.duke.edu

In order to solve layered-medium problems in areas such as microstrip antennas and monolithic microwave integrated circuits, interconnect simulations and subsurface sensing, various numerical methods such as finite difference time domain methods, finite element methods, the method of moments (MoM), and the fast multipole method (FMM), have been developed. In this work, we are concerned with piecewise homogeneous objects embedded in a layered medium. As such, the surface integral equation (SIE) can be used to reduce the number of the unknowns compared with the volume integral equation.

The SIE has been solved first with MOM and then with FMM to calculate the scattered electromagnetic fields from a homogeneous scatter with arbitrary geometry in a free space. Liu *et.al.* developed a spectral integral method (SIM) as an alternative way of solving the surface integral equation more efficiently than MOM (J. Liu and Q. H. Liu, *IEEE Micro. and Wire. Comp. Lett.*, **14**, 97-99, 2004) for arbitrarily-shaped smooth dielectric cylinders in a free space. Then Simsek *et.al.* extend to arbitrarily-shaped smooth perfect electrical conductor (PEC) and dielectric cylinders in a multilayer medium in two dimensions (E. Simsek, J. Liu, and Q. H. Liu, *IEEE Trans. Antennas Propagat.*, to be published.).

In this work we extend this method to arbitrarily-shaped smooth PEC and dielectric cylinders in a multilayer medium in three dimensions. The main ingredients of this method are the use of fast Fourier transform (FFT) algorithm and Fourier interpolation, and the subtraction of singularities in Green's functions to achieve a spectral accuracy in the integral. Layered media Green's functions for layered media are computed via numerical integration of a Sommerfeld type integral. To obtain spectral accuracy in the SIM, it is important that the Sommerfeld integration is obtained with high precision through singularity subtraction. We have demonstrated the spectral accuracy of this method and the reduced computational cost from the MOM.

