

## **Evaluation of a Modified LKB-Based Evaporation Duct Model for Stable Environments**

M.H. Newkirk\*<sup>(1)</sup>, T.R. Hanley<sup>(1)</sup>, and P.A. Frederickson<sup>(2)</sup>

(1) The Johns Hopkins University Applied Physics Laboratory, Laurel, MD

(2) The Naval Postgraduate School, Monterey, CA

A modified version of the Liu-Katsaros-Businger (LKB) model (J. Atmos. Sci., 1979) for the calculation of evaporation duct refractivity profiles developed by the Naval Postgraduate School (NPS) was recently presented (Frederickson, NRSM, 2012). This model replaced the Beljaars and Holtslag similarity functions (J. Appl. Meteorol., 1991) with those developed by Grachev, et al. (Boundary-Layer Meteorol., 2007), yielding a new variant of a model that computes more reasonable evaporation duct refractivity profiles for cases where the marine layer is strongly stable, as indicated by a strongly positive air-sea temperature difference (ASTD). In the prior implementation, meteorological conditions that created ASTD values in excess of approximately 1°C usually resulted in an unphysical solution for the refractive profile and required users to rely upon empirical models that have less of a basis in marine layer physics.

In this effort, we present the results of several comparisons between the previous and new evaporation duct models for a variety of stable cases observed during a 2010 test in the region around Wallops Island, VA. The model-generated refractive profiles for these cases are used in the Tropospheric Electromagnetic Parabolic Equation Routine (TEMPER) propagation model developed by the Johns Hopkins University / Applied Physics Laboratory (JHU/APL) to provide a quantity called the propagation factor. These results are compared to propagation factor values derived from C-band propagation link measurements in the Wallops Island area during the times of the stable cases, in order to assess the performance of the signal level predictions based on this new implementation of the LKB model.